

848E

8/4 line alphanumeric pager

A Big Screen Paging Solution



The JTECH 848E has 8 lines of big clearly readable text, or if you want, 4 lines of REALLY BIG HIGH VISIBILITY CHARACTERS.

For low light conditions, cool blue backlighting further enhances the viewing experience.

- Frequency Programmable
- Selectable Character Height, 3 or 6 mm
- 20,000+ Character Memory
- Hand Program Frequency & Address
- Urgent Call Alert Mode
- BS5839-1:2002 Compliant*

*with regard to fire paging systems for the deaf



8 line mode - 3mm text



4 line mode - 6mm text

JTECH
Australia Pty Ltd

848E

8/4 line alphanumeric pager

Main Features

- Address & frequency hand programmable (password protected)
- Storage: Repeat message rejection: optional 1,2,5,10 minutes or disabled
- Low Battery indicator
- Out of Range (NO Service) Indicator
- Repeat Message Indicator
- Error Message Indicator
- Unread Message Indicator
- Alert Modes: Vibrate, Tone, Quiet Tone & Mute
- Alert Length: 8, 16, 32 or 64 second programmable
- Urgent Call (Tone + Vibrate)
- Real Time Clock with Alarm



Specifications

Display:	High Contrast Dot Matrix LCD: 8 Line or 4 line Zoom Display
Addresses:	6 addresses (individually selectable Off/Tone/Numeric/Alpha)
Messages:	60 messages, up to 20,000+ characters
Size:	77 (L) x 53 (W) x 19 (D) mm
Weight:	56g (without battery)
Frequency ranges:	Synthesized 440-470 MHz (see ranges below)
Signalling protocol:	POCSAG
Data transmit rate:	512,1200 or 2400 baud
Sensitivity:	5 uV/m @ 512 baud, 7 uV/m @ 1200 baud
Beeper output:	Better than 80 db @ 30cm
Power:	Single AAA (LR03) battery
Model Suffix:	Frequency range K 442-448 MHz L 448-454 MHz M 454-460 MHz N 460-466 MHz P 466-472 MHz

Sydney Office - Head Office

31 MacLaurin Avenue,
East Hills NSW 2213
Ph: (02) 9792 4188
Fax: (02) 9771 3281

www.jtech.com.au

Brisbane Branch

5/139 Sandgate Road,
Albion QLD 4010
Ph: (07) 3862 4433
Fax: (07) 3862 1033