

Digital Drive Thru Communications Systems

Quail
DIGITAL



Quail Digital is the reliable way to improve the performance of your drive thru operation.

Because we're digital from the speaker post to the headset, our audio quality is the best available.

Quail Digital is fully duplex, so you can always hear your customer and take their order correctly first time...every time.

We're Europe's leading one-stop shop for your drive thru communications needs.

We provide Quail belt pack systems with a range of headsets to choose from, the Fast Track 2+ 2 lane timer, kitchen voice prompters and accessories including speaker posts, road loops and intercom backup systems.

As a drive thru operator, you'll benefit from:

- greater staff productivity
- improved order accuracy
- lower installation costs
- licence-exemption

Quail Digital offers better design:

- 18 hour belt-pack use on a 4-hour charge
- new rugged beltclip & durable rubber switches
- field-replaceable batteries
- lower maintenance costs



McDonalds Restaurants uses Quail drive thru systems

<p>QD-PS21 / 23</p>		<p>Primary Station</p> <table border="1"> <tr> <td>Operating frequency</td> <td>1.88GHz - 1.90GHz</td> </tr> <tr> <td>Power requirements</td> <td>100V - 240V, voltage sensing</td> </tr> <tr> <td>Dimensions H x W x D</td> <td>205mm x 255mm x 42mm</td> </tr> <tr> <td>Weight</td> <td>PS21 0.750kg PS23 0.800kg</td> </tr> </table>	Operating frequency	1.88GHz - 1.90GHz	Power requirements	100V - 240V, voltage sensing	Dimensions H x W x D	205mm x 255mm x 42mm	Weight	PS21 0.750kg PS23 0.800kg
Operating frequency	1.88GHz - 1.90GHz									
Power requirements	100V - 240V, voltage sensing									
Dimensions H x W x D	205mm x 255mm x 42mm									
Weight	PS21 0.750kg PS23 0.800kg									
<p>QD-BP5</p>		<p>Belt Pack Transceiver</p> <table border="1"> <tr> <td>Operating range from PS21/23</td> <td>150m outdoors, 50m indoors</td> </tr> <tr> <td>Power requirements</td> <td>Quail RB5 rechargeable battery</td> </tr> <tr> <td>Dimensions H x W x D</td> <td>94mm x 123mm x 42mm</td> </tr> <tr> <td>Weight</td> <td>0.280kg</td> </tr> </table>	Operating range from PS21/23	150m outdoors, 50m indoors	Power requirements	Quail RB5 rechargeable battery	Dimensions H x W x D	94mm x 123mm x 42mm	Weight	0.280kg
Operating range from PS21/23	150m outdoors, 50m indoors									
Power requirements	Quail RB5 rechargeable battery									
Dimensions H x W x D	94mm x 123mm x 42mm									
Weight	0.280kg									
<p>QD-CG7</p>		<p>Charger Unit (up to 4 belt packs)</p> <table border="1"> <tr> <td>Power requirements</td> <td>100V - 240V, voltage sensing</td> </tr> <tr> <td>Dimensions H x W x D</td> <td>85mm x 286mm x 193mm</td> </tr> <tr> <td>Weight</td> <td>0.485kg</td> </tr> </table>	Power requirements	100V - 240V, voltage sensing	Dimensions H x W x D	85mm x 286mm x 193mm	Weight	0.485kg		
Power requirements	100V - 240V, voltage sensing									
Dimensions H x W x D	85mm x 286mm x 193mm									
Weight	0.485kg									
<p>QD-DH5</p>		<p>Heavy Duty Drive-Thru Headset</p> <table border="1"> <tr> <td>Type</td> <td>Over-The-Head</td> </tr> <tr> <td>Mic sensitivity</td> <td>-40dBV / PA±3.5dB</td> </tr> <tr> <td>Distortion and noise</td> <td><5% THD + N</td> </tr> </table>	Type	Over-The-Head	Mic sensitivity	-40dBV / PA±3.5dB	Distortion and noise	<5% THD + N		
Type	Over-The-Head									
Mic sensitivity	-40dBV / PA±3.5dB									
Distortion and noise	<5% THD + N									
<p>QD-DH3</p>		<p>Heavy Duty Drive-Thru Headset</p> <table border="1"> <tr> <td>Type</td> <td>Over-The-Head</td> </tr> <tr> <td>Mic sensitivity</td> <td>-35dBV / PA±5dB</td> </tr> <tr> <td>Distortion and noise</td> <td><3% THD + N</td> </tr> </table>	Type	Over-The-Head	Mic sensitivity	-35dBV / PA±5dB	Distortion and noise	<3% THD + N		
Type	Over-The-Head									
Mic sensitivity	-35dBV / PA±5dB									
Distortion and noise	<3% THD + N									
<p>QD-DTM</p>		<p>Drive-Thru Module</p> <table border="1"> <tr> <td>Signal processing</td> <td>Echo cancelling <40db, noise suppression<20db</td> </tr> <tr> <td>Power requirements</td> <td>100V-240V, voltage sensing</td> </tr> <tr> <td>Dimensions H x W x D</td> <td>205mm x 255mm x 42mm</td> </tr> <tr> <td>Weight</td> <td>0.950kg</td> </tr> </table>	Signal processing	Echo cancelling <40db, noise suppression<20db	Power requirements	100V-240V, voltage sensing	Dimensions H x W x D	205mm x 255mm x 42mm	Weight	0.950kg
Signal processing	Echo cancelling <40db, noise suppression<20db									
Power requirements	100V-240V, voltage sensing									
Dimensions H x W x D	205mm x 255mm x 42mm									
Weight	0.950kg									
<p>QD-SPA</p>		<p>Speaker Post Assembly</p> <table border="1"> <tr> <td>Speaker</td> <td>4" (100cm) driver. Power handling 14 watts Impedance 8 ohms</td> </tr> <tr> <td>Microphone</td> <td>Sensitivity -38dBV/PA +/-3db. Impedance 8 ohms</td> </tr> <tr> <td>Dimensions (both) H x W x D</td> <td>150mm x 150mm x 65mm</td> </tr> </table>	Speaker	4" (100cm) driver. Power handling 14 watts Impedance 8 ohms	Microphone	Sensitivity -38dBV/PA +/-3db. Impedance 8 ohms	Dimensions (both) H x W x D	150mm x 150mm x 65mm		
Speaker	4" (100cm) driver. Power handling 14 watts Impedance 8 ohms									
Microphone	Sensitivity -38dBV/PA +/-3db. Impedance 8 ohms									
Dimensions (both) H x W x D	150mm x 150mm x 65mm									